

SINOTRUK



HOWO-TX
6X4 DUMPER

HOWO-TX 6X4 DUMPER

Type		HOWO-TX 6X4 DUMPER (RHD)
Model		ZZ3257V384GE1R
Weight	Curb Weight(KG)	16400 kg
	Payload mass(KG)	41000 kg
Dimensions	Overall Dimensions(LxWxH)(mm)	8125×2500×3160
	Wheelbase(mm)	3800+1350
	Front Overhang(mm)	1550
	Rear Overhang(mm)	900
Drive type		6×4
Cab		HOWO TX-F Cab With one sleeper bed, Single Refrigeration A/C, Manual Cab Tilting, Four-point Hydraulic Suspension
Engine	Model	MC11.40-50
	Displacement	10.518L
	Power	400HP
	Type	six cylinders in line, water-cooling, four-stroke, turbo charger with inter-cooler, direct injection
	Emission standard	Euro V
Transmission		HW19709XST+HW50 direct-coupled PTO, 9 Forwards & 1 Reverse Shifts
Chassis frame		Double-layer frame (8+8/300)
Front axle		VGD95 (drum-type) 9.5T
Rear axle		MCP16ZG double axles (i=5.92) 16Tx2
Suspension		Front and rear super strong multi-leaf springs (11/12)
Fuel Tank		400L
Tyre		12.00R20
Penrformance	Max Speed(km/h)	85km/h
	Max Gradeability(%)	>35%
Protections	Type	Metal Bumper
Cargo bucket		5800x2300x(1000+800)mm

